

28W 1500MM WARWICK T8 ROTATIONAL POULTRY TUBE

WITH ROTATABLE ENDS, CABLE AND MALE AND FEMALE CONNECTORS

50% SAVINGS
COMPARED TO
TRADITIONAL
LIGHTING

ROTATABLE TO
DIRECT LIGHT
TO WHERE IT
IS NEEDED

IMPROVES
FOOD
CONSUMPTION
RATE BY 3%

0-100%
DIMMABLE
TO SIMULATE
SUNRISE AND
SUNSET

FLICKER
FREE

5 YEAR
TOTAL
PRODUCT
WARRANTY



FEATURES AND BENEFITS

- FLICKER FREE REDUCES STRESS AND PECKING AND IMPROVES RESISTANCE TO DISEASE
- INCREASES MUSCULOSKELETAL DEVELOPMENT AND WEIGHT GAIN BY 5% (5000K)
- ENCOURAGES SEXUAL DEVELOPMENT (2700K)
- CONTROLS ONSET AND OPTIMISES EGG PRODUCTION (2700K)
- IMPROVES THE PERSISTENCE OF LAY (2700K)
- IP69K STRUCTURALLY WATERPROOF WITHOUT GLUE, DUSTPROOF AND IMPACT RESISTANT
- ROTATABLE ENDS GIVE PRECISE LIGHT DIRECTION

PRODUCT INFORMATION

Input: 180-240VAC 50/60Hz
Output Current: 520mA
Product Size (mm): 1500L x 28D
Luminous Flux: 3500 lm
Lumen Per Watt: 125 lm

Inrush Current: 9A
Flicker Free (Hz): 0
Dimmable: 0.2-100%
Surge Protection Voltage: 2000V
Cable (mm): 2 X 1.00²

PRODUCT VARIATIONS

GL7007 With rotatable ends and double ended cable and connectors (5000K) Diffused
GL7008 With rotatable ends and double ended cable and connectors (2700K) Diffused
GL7009 With rotatable ends and single ended cable and male connector (5000K) Diffused
GL7010 With rotatable ends and single ended cable and male connector (2700K) Diffused

PACKING INFORMATION

Weight (kg): 1 (GL7007, GL7008); 0.8 (GL7009, GL7010)

