

WINCHESTER 60W 10200LM IP66 LED UTILITY BATTEN LIGHT

IP66 & IK08 RATED

TOUGH & DURABLE

170LM/W EFFICIENCY

USABLE IN MANY INDOOR & OUTDOOR AREAS

OPERATING TEMPERATURE -20°C"+40°C











WINCHESTER 60W 10200LM IP66 LED UTILITY BATTEN LIGHT

FEATURES AND BENEFITS

IP66 and IK08

· Stainless steel clips

• 170Lm/W, CRI>80

· PC diffused cover

Surface mount or suspension mount

• 5 years warranty, CE, RoHS certified

PRODUCT INFORMATION

Power: 60W

Input Voltage: 200-240VAC

Input Current: 0.28A@220VAC

PF: 0.90@220VAC

CCT: 4000K

Luminous Flux: 10200Lm

Efficiency: 170Lm/W

Beam Angle: 120°

Operation Temp: -20°C"+40°C

Storage Temp: -20°C~+60°C

Life Span: Ta 40°C L70>54000 hours

IP Class: IP66

IK Class: IK08

Certificate: CE, RoHS,UKCA

Lamp Body Colour: PPC Base (Grey) + PC Cover (Diffused)

Product Size (mm): 1500*80*72mm

Installation Mode: Surface mount/Suspension mount

PRODUCT VARIATIONS

GL7603 60W Winchester LED Tri-proof Batten Light IP66 IK08 4000K 10200 Im with 316 Stainless Steel Mounting Brackets

OPTIONS

- Dimmable
- Motion Sensors
- Emergency
- 0-10V
- DALI

APPLICATION

Ideal for: service rooms, storgae rooms, outside lighting, workshops, garages and many more

FIXING OPTIONS







